



S 115 AUTOSEAL SEAMSEALER CART. 300ml

Technical Data Sheet No 703

Elastomer -based, water- and sound-proof material

It has excellent adhesion and it can be painted over immediately "wet to wet"

Resists in temperatures from (-25°C) to (+80°C) without losing it's volume

Remains permanently elastic and dries quickly

Good mechanical and chemical resistance

General Technical Description

This is a combination of elastomer and hydrocarbon resin. It is used on parts of the car body not directly exposed to UV light. It is ready to use. It remains elastic and it is adhered perfectly in non sand papered, primed or painted surfaces. It dries quickly and it can be painted over immediately "wet to wet" using synthetic paints or with one or two component acrylic paints, after drying. It can be applied with a soft or hard brush or with the cartridge.

Surface

Inside or bottom parts of the car body

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL/BODY 771 ANTISIL FAST.

Make sure the surface is air dried rather than wiped dry



Make sure you always use appropriate face protection and good ventilation

Product Application:

»» It is applied on the inside bottom parts of the car body. Applicable with a soft or hard brush. It can be painted over immediately "wet to wet" using synthetic paints or with one or two component acrylic paints, after drying. In order to enhance adhesion the application of an intermediate layer of PLASTOFIX is recommended.



Always close tin after use



Protect from humidity



Apply using the cartridge



Always wear protective equipment



Drying time
2h /23°C



Follow the application instructions mentioned in this TDS

Flash Point:
9°C / 48°F

Specific Gravity:
1.2 g/cm³

Solid Content (No thinner):
50% Weight

VOC (2004/42/EC)
This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 290 g/L.
2004/42/IIB(e)(840)290

Theoretical Coverage:
-

Cleaning of equipment:
Clean after final use with Body 740 ACRYL NORMAL

Remarks:

- Allow for additional time for combi spray booths to reach the desired temperature
- Best results when used with HB BODY PRODUCTS
- It can be used by countries that do not adopt the VOC legislation as well.

Storage shelf life:

- Store in a cool place (+5°C - +25°C) and use within 12 months for best results. Guaranteed shelf life of 24 months in unused original containers

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The SPECIAL REFINISHING PRODUCT. 1K ACRYLIC MAT PRODUCT intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 2 / 2012, August 2016