

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name: HB BODY 806 POLISHING COMPOUND****Article number: 422****1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites****Product category PC14 Metal surface treatment products, including galvanic and electroplating products****Process category PROC6 Calendering operations****Environmental release category ERC5 Industrial use resulting in inclusion into or onto a matrix****Article category AC1 Vehicles****Application of the substance / the preparation Surface protection****1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:****H.B. BODY S.A****B' ENTRANCE BLOCK 50 DA9 & MB6 Str****THESSALONIKI INDUSTRIAL AREA****57.022, SINDOS****THESSALONIKI,GREECE****Ph: +30 2310 790 000****Fax: +30 2310 790 033****www.hbbody.com****email: hbbody@hbbody.com****Further information obtainable from:****H.B. BODY S.A****B' ENTRANCE BLOCK 50 DA9 & MB6 Str****THESSALONIKI INDUSTRIAL AREA****57.022, SINDOS****THESSALONIKI,GREECE****Ph: +30 2310 790 000****Fax: +30 2310 790 033****www.hbbody.com****email: hbbody@hbbody.com****1.4 Emergency telephone number: +30 2310 790 000****SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Directive 67/548/EEC or Directive 1999/45/EC****R10: Flammable.****Information concerning particular hazards for human and environment:****The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.****Classification system:****The classification is according to the latest editions of the EU-lists adapting Directive 67/548/EEC on the classification, packaging and labelling of dangerous substances and extended by company and literature data.****2.2 Label elements****Labelling according to EU guidelines:****The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.****Risk phrases:****10 Flammable.**

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 1)

Safety phrases:

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

24 Avoid contact with skin.

29 Do not empty into drains.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.




60 This material and its container must be disposed of as hazardous waste.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3 Other hazards**Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterization: Mixtures****Description:** Mixture of hazardous substances**Dangerous components:**

Aliphatic Hydrocarbons	 Xn R65 R10-66  Flam. Liq. 3, H226  Asp. Tox. 1, H304	2.5 - <5%
------------------------	--	-----------

Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air; consult doctor in case of complaints.**After skin contact:** Generally the product does not irritate the skin.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If symptoms persist consult doctor.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**General aqueous film forming foam, Carbon dioxide (CO₂), dry chemical extinguishing powder or water spray. Do not use water.**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**Hazardous combustion products**

Fire will produce a dense black smoke containing hazardous decomposition by products. Exposure to those may be a hazard to health.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

(Contd. on page 3)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 2)

Special protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility:

As general storage guide: store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

Do not store together with explosives, gases, oxidizing solids, products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive products.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS No:	Substance	End Use	Routes of exposure	Frequency	Type	Value	Effect
123-86-4	Butyl Acetate	Workers	Inhalation		Long Term	Systemic	Effect
	100mg/kg						

Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 3)

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:** Wash hands before breaks and at the end of work.**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Liquid

Colour:

White

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value:

Not determined.

Change in condition**Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

100 °C

Flash point:

21 - 55 °C

(Contd. on page 5)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 4)

Flammability (solid, gaseous):	Not applicable.
Autoignition temperature:	
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Risk of explosion by shock, friction, fire or other sources of ignition.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 20 °C:	23 hPa
Density at 20 °C:	1.42 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
Water:	50.0 %
VOC (EC)	120 g/l
Solids content (volume):	40.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity****10.2 Chemical stability**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity:****Primary irritant effect:**

on the skin: No irritant effect.

on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

GB
(Contd. on page 6)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 5)

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential

This product is not known to have bioaccumulative potentials. It should not be disposed in areas where living organisms could consume. Dispose it as a hazardous material according to local laws and regulations

12.4 Mobility in soil

This product is not considered to present any mobility in soil. Do not dispose it in the soil and treat it as a hazardous product according to local laws and legislations.

Additional ecological information:**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

12.6 Other adverse effects No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN-Number**

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT, special provision 640E

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR



Class

3 (F1) Flammable liquids.

Label

3

(Contd. on page 7)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 6)

IMDG, IATA



Class	3 Flammable liquids.
Label	3

14.4 Packing group ADR, IMDG, IATA	III
---------------------------------------	-----

14.5 Environmental hazards: Marine pollutant:	No
--	----

14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
---	-----------------

Transport/Additional information:

ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E

UN "Model Regulation":	UN1263, PAINT, special provision 640E, 3, III
------------------------	---

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Risk phrases:

10 Flammable.

Safety phrases:

23 Do not breathe the gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

24 Avoid contact with skin.

29 Do not empty into drains.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

60 This material and its container must be disposed of as hazardous waste.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

R10 Flammable.

(Contd. on page 8)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 7)

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

Department issuing MSDS: Department of Quality Control

Contact:

H.B BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

* Data compared to the previous version altered.

GB

(Contd. on page 9)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 8)

Annex: Exposure scenario

Short title of the exposure scenario

General Statement: The exposure scenarios on the MSDS tend to provide specific information on how a hazardous substance, found in a preparation or as a raw material can be managed and controlled. It considers specific conditions of use in order to ensure that a use can be safe to humans and the environment. Identified risk management measures are to be implemented unless the downstream user is able to ensure a safe handling of the material in a different way.

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC14 Metal surface treatment products, including galvanic and electroplating products

Process category PROC6 Calendering operations

Article category AC1 Vehicles

Environmental release category ERC5 Industrial use resulting in inclusion into or onto a matrix

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency

5 workdays/week.

Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture The substance is main component.

Other operational conditions

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting consumer exposure No special measures required.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Organisational protective measures

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

No special measures required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

(Contd. on page 10)

Trade name: HB BODY 806 POLISHING COMPOUND

(Contd. of page 9)

Exposure estimation

Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.