

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**Trade name: **BODY 250 FIBER SOFT POLYESTER FILLER**

Article number: 251

1.2 Relevant identified uses of the substance or mixture and uses advised against**Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category

PC9b Fillers, putties, plasters, modelling clay

PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Environmental release category ERC2 Formulation of preparations

Article category AC1 Vehicles

Application of the substance / the preparation

Filler/ Extender

Surface protection

Fiberglass 2K polyester filler

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

H.B. BODY S.A

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

H.B. BODY S.A

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

1.4 Emergency telephone number: +30 2310 790 000**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20: Harmful by inhalation.



Xi; Irritant

R36/38: Irritating to eyes and skin.

R10: Flammable.

(Contd. on page 2)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 1)

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists addapting Directive 67/548/EEC on the classification, packaging and labelling of dangerous substances and extended by company and literature data.

2.2 Label elements**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xn Harmful

Hazard-determining components of labelling:

styrene

Risk phrases:

- 10 Flammable.
- 20 Harmful by inhalation.
- 36/38 Irritating to eyes and skin.

Safety phrases:

- 9 Keep container in a well-ventilated place.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29 Do not empty into drains.
- 36/37 Wear suitable protective clothing and gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

2.3 Other hazards**Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterization: Mixtures**

Description: Mixture of hazardous substances

Dangerous components:

CAS: 100-42-5	styrene	20 - <25%
EINECS: 202-851-5	☒ Xn R20	
Index number: 601-026-00-0	☒ Xi R36/38	
RTECS: WL 3675000	R10	
Reg.nr.: 01-2119457861-32-0011	☒ Flam. Liq. 3, H226	
01-2119457861-32-0009	☒ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	LUVOTIX R - RF (THIXCIN GR)	< 2.5%
	☒ Flam. Liq. 3, H226	

Additional information: For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 3)

Trade name: **BODY 250 FIBER SOFT POLYESTER FILLER**

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

General aqueous film forming foam, Carbon dioxide (CO₂), dry chemical extinguishing powder or water spray. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

Hazardous combustion products

Fire will produce a dense black smoke containing hazardous decomposition by products. Exposure to those may be a hazard to health.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Special protective equipment and fire fighting procedures:

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 3)

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Observe label precautions. Store between 5 and 25 degrees Celcius in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent access from unauthorised personell. Containers which are opened must be carefully resealed and kept upright to prevent leakage. The storage and use of this product is subject to the requirements of the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). Up to 250 litres of such flammable liquids may be stored in a work area provided they are kept in a fire-proof cupboard or bin. Larger quantities must be kept in a separate storeroom conforming to the structural requirements of the regulations. Further guidance is contained in the HSE ACOP L135, "Storage of Dangerous Substances." UK.

Information about storage in one common storage facility:

As general storage guide: store separately from oxidizing agents and strongly alkaline and strongly acidic materials. Do not store together with explosives, gases, oxidizing solids, products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive products.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection**

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:**

100-42-5 styrene

WEL	Short-term value: 1080 mg/m ³ , 250 ppm
	Long-term value: 430 mg/m ³ , 100 ppm

DNELs

CAS No:	Substance	End Use	Routes of exposure	Frequency	Type	Value	Systemic	Effect
123-86-4	Butyl Acetate	Workers	Inhalation		Long Term	100mg/kg		

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

(Contd. on page 5)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Pasty

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value:

Not determined.

Change in condition**Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

145 °C

Flash point:

21 - 55 °C

Flammability (solid, gaseous):

Not applicable.

Autoignition temperature:

480 °C

Decomposition temperature:

Not determined.

Self-igniting:

Product is not selfigniting.

Danger of explosion:

Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits:**Lower:**

1.2 Vol %

Upper:

8.9 Vol %

(Contd. on page 6)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 5)

Vapour pressure at 20 °C:	6 hPa
Density at 20 °C:	1.453 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	20.0 %
VOC (EC)	110 g/l 110.0 g/l
Solids content (volume):	80.0 %

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity****10.2 Chemical stability**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****100-42-5 styrene**

Oral LD50 5000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

471-34-1 calcium carbonate

Oral LD50 6450 mg/kg (rat)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: Irritating effect.

Sensitization: Sensitizing effect through inhalation is possible by prolonged exposure.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential

This product is not known to have bioaccumulative potentials. It should not be disposed in areas where living organisms could consume. Dispose it as a hazardous material according to local laws and regulations

12.4 Mobility in soil

This product is not considered to present any mobility in soil. Do not dispose it in the soil and treat it as a hazardous product according to local laws and legislations.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT, special provision 640E

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR




Class

3 (F1) Flammable liquids.

(Contd. on page 8)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 7)

Label	3
IMDG, IATA	
	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
UN "Model Regulation":	UN1263, PAINT, special provision 640E, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xn Harmful

Hazard-determining components of labelling:

styrene

Risk phrases:

- 10 Flammable.
- 20 Harmful by inhalation.
- 36/38 Irritating to eyes and skin.

Safety phrases:

- 9 Keep container in a well-ventilated place.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29 Do not empty into drains.
- 36/37 Wear suitable protective clothing and gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

(Contd. on page 9)

Printing date 15.10.2013

Revision: 15.10.2013

Version number 34

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

R10 Flammable.

R20 Harmful by inhalation.

R36/38 Irritating to eyes and skin.

Department issuing MSDS: Department of Quality Control

Contact:

H.B BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

* Data compared to the previous version altered.

GB

(Contd. on page 10)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 9)

Annex: Exposure scenario 1**Short title of the exposure scenario**

General Statement: The exposure scenarios on the MSDS tend to provide specific information on how a hazardous substance, found in a preparation or as a raw material can be managed and controlled. It considers specific conditions of use in order to ensure that a use can be safe to humans and the environment. Identified risk management measures are to be implemented unless the downstream user is able to ensure a safe handling of the material in a different way.

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category

PC9b Fillers, putties, plasters, modelling clay

PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Article category AC1 Vehicles

Environmental release category ERC2 Formulation of preparations

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid**Concentration of the substance in the mixture** The substance is main component.**Other operational conditions****Other operational conditions affecting environmental exposure** No special measures required.**Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Other operational conditions affecting consumer exposure No special measures required.**Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures Ensure that suitable extractors are available on processing machines**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

(Contd. on page 11)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 10)

Environmental protection measures**Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer This product is to be used by professional technicians only.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB

(Contd. on page 12)

Trade name: BODY 250 FIBER SOFT POLYESTER FILLER

(Contd. of page 11)

Annex: Exposure scenario 2

Short title of the exposure scenario

General Statement: The exposure scenarios on the MSDS tend to provide specific information on how a hazardous substance, found in a preparation or as a raw material can be managed and controlled. It considers specific conditions of use in order to ensure that a use can be safe to humans and the environment. Identified risk management measures are to be implemented unless the downstream user is able to ensure a safe handling of the material in a different way.

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture Raw material.

Other operational conditions

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Other operational conditions affecting consumer exposure Keep out of the reach of children.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer This product is to be used by professional technicians only.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.