

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

Article number: 372

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Environmental release category ERC2 Formulation of preparations

Article category AC1 Vehicles

Application of the substance / the mixture

Hardening agent/ Curing agent

Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

H.B. BODY S.A

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

H.B. BODY S.A

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

1.4 Emergency telephone number:

HEAD OFFICES: MONDAY -FRIDAY 8am-4pm

Ph: 0030 2310 790 000

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Sensitising

R43: May cause sensitisation by skin contact.



F; Highly flammable

R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 2)

Trade name: **BODY H735 FAST HARDENER VOC COMPLIANT**

(Contd. of page 1)

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists addapting Directive 67/548/EEC on the classification, packaging and labelling of dangerous substances and extended by company and literature data.

2.2 Label elements**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xi Irritant
F Highly flammable

Hazard-determining components of labelling:

Isocyanates

Risk phrases:

- 11 Highly flammable.
- 43 May cause sensitisation by skin contact.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 24/25 Avoid contact with skin and eyes.
- 29 Do not empty into drains.
- 33 Take precautionary measures against static discharges.
- 37 Wear suitable gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

2.3 Other hazards**Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterization: Mixtures

Description: Mixture of hazardous substances

Dangerous components:

(Contd. on page 3)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 2)

CAS: 28182-81-2 NLP: 500-060-2	Isocyanates ❌ Xi R43 R52/53 ⚠ Skin Sens. 1, H317 Aquatic Chronic 3, H412	50 - <60%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 RTECS: SA 9275000 Reg.nr.: 01-2119473980-30-0002	4-methylpentan-2-one ❌ Xn R20 ❌ Xi R36/37 🔥 F R11 R66 ⚠ Flam. Liq. 2, H225 ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	15 - <20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000 Reg.nr.: 01-2119485493-29-007 01-2119485493-29-004 01-2119485493-29-003 01-2119485493-29-005 01-2119485493-29	n-butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	10 - <15%
CAS: 110-19-0 EINECS: 203-745-1 Index number: 607-026-00-7 Reg.nr.: 01-2119488971-22-001	isobutyl acetate 🔥 F R11 R66 ⚠ Flam. Liq. 2, H225	10 - <15%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 RTECS: MO 1740000	hexamethylene-di-isocyanate ☠ T R23 ❌ Xn R42/43 ❌ Xi R36/37/38 ⚠ Acute Tox. 3, H331 ⚠ Resp. Sens. 1, H334 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	< 2.5%

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

General aqueous film forming foam, Carbon dioxide (CO₂), dry chemical extinguishing powder or water spray. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 3)

Hazarous combustion products

Fire will produce a dense black smoke containing hazardous decomposition by products. Exposure to those may be a hazard to health.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

As general storage guide: store separately from oxidizing agents and strongly alkaline and strongly acidic materials. Do not store together with explosives, gases, oxidizing solids, products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive products.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 4)

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-10-1 4-methylpentan-2-one	
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
110-19-0 isobutyl acetate	
WEL	Short-term value: 903 mg/m ³ , 187 ppm Long-term value: 724 mg/m ³ , 150 ppm
822-06-0 hexamethylene-di-isocyanate	
WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO

DNELs

CAS No:	Substance	End Use	Routes of exposure	Frequency	Type	Value	Systemic	Effect
123-86-4	Butyl Acetate	Workers	Inhalation		Long Term	100mg/kg		

Ingredients with biological limit values:

108-10-1 4-methylpentan-2-one	
BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

(Contd. on page 6)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 5)

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 114 °C

Flash point: ≤ 21 °C

Flammability (solid, gaseous): Not applicable.

Autoignition temperature: 370 °C

Decomposition temperature: Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits:

Lower: 1.2 Vol %

Upper: 10.5 Vol %

Vapour pressure at 20 °C: 20 hPa

Density at 20 °C: 1.02308 g/cm³

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 7)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 6)

Solvent content:

Organic solvents:	43.2 %
VOC (EC)	441.8 g/l

Solids content (volume):	52.8 %
---------------------------------	--------

9.2 Other information	No further relevant information available.
------------------------------	--

SECTION 10: Stability and reactivity**10.1 Reactivity****10.2 Chemical stability****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****108-10-1 4-methylpentan-2-one**

Oral	LD50	2080 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

123-86-4 n-butyl acetate

Oral	LD50	13100 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21.0 mg/l (rat)

110-19-0 isobutyl acetate

Oral	LD50	13400 mg/kg (rat)
------	------	-------------------

822-06-0 hexamethylene-di-isocyanate

Oral	LD50	738 mg/kg (rat)
Dermal	LD50	593 mg/kg (rat)

Primary irritant effect:**on the skin:** No irritant effect.**on the eye:** No irritating effect.**Sensitization:** Sensitization possible through skin contact.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

(Contd. on page 8)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 7)

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential

This product is not known to have bioaccumulative potentials. It should not be disposed in areas where living organisms could consume. Dispose it as a hazardous material according to local laws and regulations

12.4 Mobility in soil

This product is not considered to present any mobility in soil. Do not dispose it in the soil and treat it as a hazardous product according to local laws and legislations.

Ecotoxicological effects:

Remark: Harmful to fish

Additional ecological information:**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

12.6 Other adverse effects No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN-Number**

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT RELATED MATERIAL, special provision 640D

IMDG, IATA

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR



Class
Label

3 (F1) Flammable liquids.
3

IMDG, IATA



Class
Label

3 Flammable liquids.
3

(Contd. on page 9)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 8)

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

33

EMS Number:

F-E,S-E**14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Transport category

2

Tunnel restriction code

D/E

UN "Model Regulation":

UN1263, PAINT RELATED MATERIAL, special provision 640D, 3, II

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xi Irritant

F Highly flammable

Hazard-determining components of labelling:

Isocyanates

Risk phrases:

11 Highly flammable.

43 May cause sensitisation by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

24/25 Avoid contact with skin and eyes.

29 Do not empty into drains.

33 Take precautionary measures against static discharges.

37 Wear suitable gloves.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

51 Use only in well-ventilated areas.

60 This material and its container must be disposed of as hazardous waste.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

GB

(Contd. on page 10)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 9)

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R23	Toxic by inhalation.
R36/37	Irritating to eyes and respiratory system.
R36/37/38	Irritating to eyes, respiratory system and skin.
R42/43	May cause sensitisation by inhalation and skin contact.
R43	May cause sensitisation by skin contact.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Department issuing MSDS: Department of Quality Control

Contact:

H.B BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

*** Data compared to the previous version altered.**

(Contd. of page 10)

^{GB}
(Contd. on page 12)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 11)

Annex: Exposure scenario**Short title of the exposure scenario**

General Statement: The exposure scenarios on the MSDS tend to provide specific information on how a hazardous substance, found in a preparation or as a raw material can be managed and controlled. It considers specific conditions of use in order to ensure that a use can be safe to humans and the environment. Identified risk management measures are to be implemented unless the downstream user is able to ensure a safe handling of the material in a different way.

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Article category AC1 Vehicles

Environmental release category ERC2 Formulation of preparations

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture The substance is main component.

Other operational conditions

Other operational conditions affecting environmental exposure Use only on hard ground.

Other operational conditions affecting worker exposure

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure No special measures required.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures**Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures**Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

(Contd. on page 13)

Trade name: BODY H735 FAST HARDENER VOC COMPLIANT

(Contd. of page 12)

Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer This product is to be used by professional technicians only.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.