

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **BODY 2K INDUSTRIAL PAINT**

Article number: 95

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Environmental release category ERC2 Formulation of preparations

Article category AC2 Machinery, mechanical appliances, electrical/electronic articles

Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

H.B. BODY S.A
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com

Further information obtainable from:

H.B. BODY S.A
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com

1.4 Emergency telephone number: +30 2310 790 000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

R61: May cause harm to the unborn child.



Xn; Harmful

R20/21-40-48/20-62-65: Harmful by inhalation and in contact with skin. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility. Harmful: may cause lung damage if swallowed.



Xi; Irritant

R38: Irritating to skin.



F; Highly flammable

R11: Highly flammable.

(Contd. on page 2)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 1)

**N; Dangerous for the environment****R51/53:** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**R33:** Danger of cumulative effects.**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists adapting Directive 67/548/EEC on the classification, packaging and labelling of dangerous substances and extended by company and literature data.

2.2 Label elements**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:**T** Toxic**F** Highly flammable**N** Dangerous for the environment**Hazard-determining components of labelling:**

toluene

Lead sulfochromate yellow

xylene

Risk phrases:

61 May cause harm to the unborn child.

11 Highly flammable.

20/21 Also harmful by inhalation and in contact with skin.

33 Danger of cumulative effects.

38 Irritating to skin.

40 Limited evidence of a carcinogenic effect.

48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.

62 Possible risk of impaired fertility.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

Safety phrases:

53 Avoid exposure - obtain special instructions before use.

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking.

20 When using do not eat or drink.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

25 Avoid contact with eyes.

29 Do not empty into drains.

33 Take precautionary measures against static discharges.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

57 Use appropriate container to avoid environmental contamination.

60 This material and its container must be disposed of as hazardous waste.

Special labelling of certain preparations:

Contains butanone oxide. May produce an allergic reaction.

Restricted to professional users.

2.3 Other hazards**Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

(Contd. on page 3)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 2)

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterization: Mixtures**

Description: Mixture of hazardous substances

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 01-2119488216-32-001 01-2119488216-32-002 01-2119488216-32-003	xylene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	20 - <25%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 RTECS: XS 5250000 Reg.nr.: 01-2119471310-51-0000 01-2119471310-51-0003 01-2119471310-51-0005 01-2119471310-51-0002 01-2119471310-51-0027	toluene Xn R48/20-63-65 Xi R38 F R11 R67 Repr. Cat. 3 Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	15 - <20%
CAS: 1344-37-2 EINECS: 215-693-7 Index number: 082-009-00-X	Lead sulfochromate yellow T Repr. Cat. 1, 3 R61 Xn R62-40 N R50/53 R33 Carc. Cat. 3 Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	15 - <20%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-0001	Solvent naphtha (petroleum), light arom. Xn R65 Xi R37 N R51/53 R10 Carc. Cat. 2 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; STOT SE 3, H335	2.5 - <5%
	butanone oxide Xi R36 Xi R43 Eye Irrit. 2, H319; Skin Sens. 1, H317	< 2.5%

SVHC

1344-37-2 | Lead sulfochromate yellow

Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 3)

It is highly recommended to avoid the inhalation of vapor, mist or dust. In any case of accidental inhalation of vapors move to open fresh air. In any case of irregular breathing administer first aid and artificial respiration. If symptoms persist seek medical physician at once.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

In case of skin contact DO NOT clean effected area with solvents or thinners. Take off all contaminated clothing at once. Wash skin thoroughly with neutral pH soap and water. In any suspicion that skin irritation persists call a doctor.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

General aqueous film forming foam, Carbon dioxide (CO₂), dry chemical extinguishing powder or water spray. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

Hazarous combustion products

Fire will produce a dense black smoke containing hazardous decomposition by products. Exposure to those may be a hazard to health.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Speial protective equipment and fire fighting procedures:

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 5)

Trade name: **BODY 2K INDUSTRIAL PAINT**

(Contd. of page 4)

Protect against electrostatic charges.
Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

As general storage guide: store separately from oxidizing agents and strongly alkaline and strongly acidic materials. Do not store together with explosives, gases, oxidizing solids, products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive products.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
108-88-3 toluene	
WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
1344-37-2 Lead sulfochromate yellow	
WEL	Long-term value: 0.05 mg/m ³ as Cr; Carc, Sen

DNELs

CAS No:	Substance	End Use	Routes of exposure	Frequency	Type	Value
123-86-4	Butyl Acetate	Workers	Inhalation	Long Term	Systemic Effect	100mg/kg

Ingredients with biological limit values:

1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
1344-37-2 Lead sulfochromate yellow	
BMGV	10 µmol/mol creatinine Medium: urine Sampling time: post shift Parameter: chromium

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 6)

Trade name: **BODY 2K INDUSTRIAL PAINT**

(Contd. of page 5)

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value:

Not determined.

Change in condition**Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

110 °C

Flash point:

≤ 21 °C

Flammability (solid, gaseous):

Not applicable.

Autoignition temperature:

500 °C

Decomposition temperature:

Not determined.

(Contd. on page 7)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 6)

Self-igniting:	Product is not selfigniting.
Danger of explosion:	Risk of explosion by shock, friction, fire or other sources of ignition.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20 °C:	29 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	42.3 %
VOC (EC)	423.4 g/l
Solids content (volume):	55.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity****10.2 Chemical stability**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:**

1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50 (static)	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)
1344-37-2 Lead sulfochromate yellow		
Oral	LD50	>10000 mg/kg (rat)

(Contd. on page 8)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 7)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: No irritating effect.

Sensitization: Sensitizing effect through inhalation is possible by prolonged exposure.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential

This product is not known to have bioaccumulative potentials. It should not be disposed in areas where living organisms could consume. Dispose it as a hazardous material according to local laws and regulations

12.4 Mobility in soil

This product is not considered to present any mobility in soil. Do not dispose it in the soil and treat it as a hazardous product according to local laws and legislations.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:**General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1263

(Contd. on page 9)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 8)

14.2 UN proper shipping name**ADR**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS, special provision 640D

IMDG

PAINT (Lead sulfochromate yellow, STYRENE MONOMER, STABILIZED), MARINE POLLUTANT

IATA

PAINT

14.3 Transport hazard class(es)**ADR****Class
Label****3 (F1) Flammable liquids.
3****IMDG****Class
Label****3 Flammable liquids.
3****IATA****Class
Label****3 Flammable liquids.
3****14.4 Packing group****ADR, IMDG, IATA****II****14.5 Environmental hazards:****Product contains environmentally hazardous substances: Lead sulfochromate yellow****Marine pollutant:****Yes****Special marking (ADR):****Symbol (fish and tree)****Symbol (fish and tree)****14.6 Special precautions for user****Warning: Flammable liquids.****Danger code (Kemler):****33****EMS Number:****F-E,S-E****14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code****Not applicable.****Transport/Additional information:****ADR****Limited quantities (LQ)****5L****Transport category****2****Tunnel restriction code****D/E****UN "Model Regulation":****UN1263, PAINT, special provision 640D, ENVIRONMENTALLY HAZARDOUS, 3, II**

(Contd. on page 10)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 9)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

T Toxic

F Highly flammable

N Dangerous for the environment

Hazard-determining components of labelling:

toluene

Lead sulfochromate yellow

xylene

Risk phrases:

- 61 May cause harm to the unborn child.
- 11 Highly flammable.
- 20/21 Also harmful by inhalation and in contact with skin.
- 33 Danger of cumulative effects.
- 38 Irritating to skin.
- 40 Limited evidence of a carcinogenic effect.
- 48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 62 Possible risk of impaired fertility.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

Safety phrases:

- 53 Avoid exposure - obtain special instructions before use.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 20 When using do not eat or drink.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 25 Avoid contact with eyes.
- 29 Do not empty into drains.
- 33 Take precautionary measures against static discharges.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 57 Use appropriate container to avoid environmental contamination.
- 60 This material and its container must be disposed of as hazardous waste.

Special labelling of certain preparations:

Contains butanone oxide. May produce an allergic reaction.

Restricted to professional users.

National regulations:**Other regulations, limitations and prohibitive regulations****Substances of very high concern (SVHC) according to REACH, Article 57**

1344-37-2 | Lead sulfochromate yellow

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.

(Contd. on page 11)

Trade name: **BODY 2K INDUSTRIAL PAINT**

(Contd. of page 10)

- H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H350 May cause cancer.
 H360Df May damage the unborn child. Suspected of damaging fertility.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
 R11 Highly flammable.
 R20/21 Harmful by inhalation and in contact with skin.
 R33 Danger of cumulative effects.
 R36 Irritating to eyes.
 R37 Irritating to respiratory system.
 R38 Irritating to skin.
 R40 Limited evidence of a carcinogenic effect.
 R43 May cause sensitisation by skin contact.
 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R61 May cause harm to the unborn child.
 R62 Possible risk of impaired fertility.
 R63 Possible risk of harm to the unborn child.
 R65 Harmful: may cause lung damage if swallowed.
 R67 Vapours may cause drowsiness and dizziness.

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 1B H350 May cause cancer.
 Repr. 1A H360Df May damage the unborn child. Suspected of damaging fertility.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.

Department issuing MSDS: Department of Quality Control**Contact:**

H.B BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

(Contd. on page 12)

Printing date 25.02.2014

Revision: 25.02.2014

Version number 2

Trade name: BODY 2K INDUSTRIAL PAINTemail: stamkou@hbbody.com

(Contd. of page 11)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

*** Data compared to the previous version altered.**

GB

(Contd. on page 13)

Trade name: BODY 2K INDUSTRIAL PAINT

(Contd. of page 12)

Annex: Exposure scenario**Short title of the exposure scenario**

General Statement: The exposure scenarios on the MSDS tend to provide specific information on how a hazardous substance, found in a preparation or as a raw material can be managed and controlled. It considers specific conditions of use in order to ensure that a use can be safe to humans and the environment. Identified risk management measures are to be implemented unless the downstream user is able to ensure a safe handling of the material in a different way.

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture The substance is main component.

Other operational conditions

Other operational conditions affecting environmental exposure Use only on hard ground.

Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure No special measures required.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures**Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures**Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer This product is to be used by professional technicians only.