



# BODY HYD 100

Technical Data Sheet No 713

## General Technical Description

100% acrylic waterborne sealant

Waterborne sealant for corrosion protection and sound proofing of car bodies

Easy to use

## Surface

Underbody parts of cars that require anticorrosive protection

## Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL / BODY 771 ANTISIL FAST

Make sure the surface is air dried rather than wiped dry



Make sure you always use appropriate face protection and good ventilation

**Product Application:** » Sound proof, anticorrosive material, which also protects from stone-chipping. Suitable for application on the interior and exterior underparts of cars, trunk and baggage compartments of buses. It can also be used as a primer and be rubbed with water, when one wishes to insulate a relatively recently painted surface, and repaint it in a few hours. It can be used as an imitation of leather sky. It dries fast, it can be used with all paint systems. In order to effect a relief surface, apply the material without any addition of thinner, using a spray gun with a 4 mm nozzle diameter and a pressure of 5-6 bar.



0%



0%



4mm  
5-6 bar



22s  
DIN 4 / 20°C



or apply with brush



1.5mm  
3-4 bar  
2 x 50µm



26-h / 20°C  
30min / 60°C



26-h / 20°C  
30min / 60°C



Always wear protective equipment



Follow the application instructions mentioned in this TDS

## Flash Point:

-

## Specific Gravity:

1.28 - 1.36 g/cm<sup>3</sup>

## Solid Content (No thinner):

62±5% Weight

## VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 50 g/L.  
2004/42/IIB(e)(840)50

## Theoretical Coverage:

-

## Cleaning of equipment:

Clean after final use with plenty of water

## Remarks:

- Best results when used with HB BODY PRODUCTS.
- It can be used by countries that do not adopt the VOC legislation as well.

## Storage shelf life:

- Store in a cool place (+5°C - +25°C) and use within 12 months for best results. Guaranteed shelf life of 18 months in unused original containers.

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 2/2015, November 2015